

**UT106****Automotive Multi-Purpose Meters****SPECIFICATIONS**

| Basic Functions                            | Range                        | Best Accuracy |
|--|------------------------------|---------------|
| DC Voltage                                 | 200mV/2V/20V/200V/1000V      | ±(0.5%+2)     |
| AC Voltage                                 | 200V/750V                    | ±(0.8%+5)     |
| DC Current                                 | 200mA/10A                    | ±(0.8%+5)     |
| Resistance                                 | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | ±(0.8%+5)     |
| Temperature (°C)                           | -40°C~1000°C                 | ±(2%+8)       |
| Frequency                                  | 2kHz                         | ±(2%+5)       |
| Special Functions                          |                              |               |
| Fused 10A Range                            |                              | ✓             |
| Dwell                                      | 4Cyl/6Cyl/8Cyl               | ±(3%+5)       |
| Tach                                       | 4Cyl/6Cyl/8Cyl               | ±(3%+5)       |
| Diode                                      |                              | ✓             |
| Continuity Buzzer                          |                              | ✓             |
| Data Hold                                  |                              | ✓             |
| Low Battery Display                        |                              | ✓             |
| Input Impedance for DC Voltage Measurement | Around 10MΩ                  | ✓             |
| Max. Display                               | 1999                         | ✓             |

**GENERAL CHARACTERISTICS**

|                              |  |
|------------------------------|--|
| Power                        | 9V Battery (6F22)  |
| LCD Size                     | 60 x 54 mm   |
| Product Colour               | UT106 - Grey, Holster - Red  |
| Product Net Weight           | 352g   |
| Product Size                 | 179 x 88 x 39 mm   |
| Standard Accessories         | Test Lead, Battery, English Manual, Holster, Point Contact Temperature Probe |
| Standard Individual Packing  | Gift Box   |
| Standard Quantity Per Carton | 30 pcs   |
| Standard Carton Measurement  | 490 x 425 x 300 mm<br>(0.062 CBM Per Standard Carton)                        |
| Standard Carton Gross Weight | 23kg   |

\*Available at Extra Cost

Specifications and other information are subject to change without further notice.