

UT10A

Modern Pocket-Size Digital Multimeters



CE

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/300V	±(0.8%+1)
AC Voltage	4V/40V/300V	±(1.2%+3)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Capacitance	4nF/40nF/400nF/4μF/40μF/200μF	±(4%+3)
Frequency	10Hz/100kHz	±(0.5%+3)
Special Functions		
Auto Ranging	✓	
Duty Cycle	0.1%~99.9%	
Diode	✓	
Continuity Buzzer	✓	
Relative Mode	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	10MΩ	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	3V Button Battery (CR2032)
LCD Size	43 x 22 mm
Product Colour	Red and Grey
Product Net Weight	62g
Product Size	58 x 108 x 12mm
Standard Accessories	Test Lead, Battery, English Manual, Vinyl Holder
Standard Individual Packing	Blister
Standard Quantity Per Carton	90 pcs
Standard Carton Measurement	Around 545 x 305 x 425mm (0.071CBM Per Standard Carton)
Standard Carton Gross Weight	Around 11.25kg

Specifications and other information are subject to change without further notice.