



SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/500V	±(0.8%+1)
AC Voltage	4V/40V/400V/500V	±(1.2%+3)
DC Current	400µA/4000µA/40mA/400mA/4A/10A	±(1%+2)
AC Current	400µA/4000µA/40mA/400mA/4A/10A	±(1.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Special Functions		
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max. Display	3999	

GENERAL CHARACTERISTICS

Power	1.5V Battery (AAA) x 2
LCD Size	48 x 16mm
Product Colour	Red and Grey
Product Net Weight	Around 156g
Product Size	130 x 73.5 x 35 mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	60 pcs
Standard Carton Measurement	Around 486 x 345 x 310 mm (Around 0.052 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 18kg

*Available at Extra Cost
Specifications and other information are subject to change without further notice.