



SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	± (0.05%+3)
AC Voltage	2V/20V/200V/750V	± (0.5%+10)
DC Current	2mA/200mA/20A	± (0.5%+5)
AC Current	2mA/200mA/20A	± (0.8%+5)
Resistance	200Ω/2kΩ/20kΩ/2MΩ/20MΩ	± (0.3%+1)
Capacitance	2nF/20nF/200nF/20μF	± (4%+3)
Frequency	2kHz/20kHz	± (1.5%+5)
Special Functions		
Diode	✓	
Continuity Buzzer	✓	
Transistor	✓	
Data Hold	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max. Display	19999	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	61 x 32 mm
Product Colour	UT39E-Grey Holster Red
Product Net Weight	Around 310g (Including Holster)
Product Size	172 x 83 x 38mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	594 x 414 x 334mm (0.082CBM Per Standard Carton)
Standard Carton Gross Weight	Around 21.4kg

*Available at Extra Cost
 Specifications and other information are subject to change without further notice.