

UT60D**Modern Digital Multimeters****SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
DC Voltage	340mV/3.4V/34V/340V/1000V	±(0.8%+1)
AC Voltage	3.4V/34V/340V/750V	±(1.5%+3)
Bandwidth	100kHz-3db	
DC Current	340μA/3400μA/34mA/340mA/10A	±(1.2%+2)
AC Current	340μA/3400μA/34mA/340mA/10A	±(1%+3)
Resistance	340Ω/3.4kΩ/34kΩ/340kΩ/3.4MΩ/34MΩ	±(1%+2)
Frequency	3.4kHz/34kHz/340kHz/3.4MHz/34MHz	±(0.2%+2)
RPM	34k/340k/3.4M/34M/340M	±(0.2%+2)
Special Functions		
Fused 10A Range	✓	
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Data Hold	✓	
RS232C	✓	
Display Backlight	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for Voltage Measurement	Around 10MΩ	
Max. Display	3400	

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	63 x 31mm
Product Colour	Red and Grey
Product Net Weight	320g
Product Size	177 x 85 x 40mm
Standard Accessories	Test Lead, Battery, English Manual, Test Clip, RS232C Interface Cable, Software
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Packing	Gift Box
Standard Quantity Per Carton	40 pcs
Standard Carton Measurement	595 x 400 x 326mm (0.078 CBM Per Standard Carton)
Standard Carton Gross Weight	24.2kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.