

UT71A**Intelligent Digital Multimeters**

CE

SPECIFICATIONS

| Basic Functions | Range | Best Accuracy |
|----------------------------|---|-----------------|
| DC Voltage | 200mV/2V/20V/200V/1000V | $\pm(0.1\%+8)$ |
| AC Voltage | 2V/20V/200V/1000V | $\pm(0.8\%+40)$ |
| AC Bandwidth | 100KHz | ✓ |
| DC Current | 200 μ A/2000 μ A/20A/200mA/10A | $\pm(1\%+20)$ |
| AC Current | 200 μ A/2000 μ A/20A/200mA/10A | $\pm(0.5\%+50)$ |
| Resistance | 200 Ω /2k Ω /20k Ω /200k Ω /2M Ω /20M Ω | $\pm(1.5\%+20)$ |
| Capacitance | 20nF/200nF/2 μ F/20 μ F/200 μ F/2mF/20mF | $\pm(0.1\%+20)$ |
| Temperature($^{\circ}$ C) | -40 $^{\circ}$ C~1000 $^{\circ}$ C | |
| Temperature($^{\circ}$ F) | -40 $^{\circ}$ F~1832 $^{\circ}$ F | |
| Frequency | 20Hz/200Hz/2kHz/20kHz /200KHz/2MHz/20MHz/200MHz | $\pm(0.1\%+15)$ |
| Duty Cycle | 10%~90% | $\pm(1\%+30)$ |
| 4~20mA Loop | 0%~100% | |
| Power Measurement | | |
| Special Functions | | |
| Fused 10A Range | | ✓ |

| | |
|-------------------------------------|--|
| Product Net Weight | 384g |
| Product Size | 200 x 93 x 40mm |
| Standard Accessories | Test Lead, Battery, English Manual, Alligator Clip, Test Clip, USB Interface Cable, Software, Carrying Bag |
| Standard Individual Packing | Gift Box |
| Standard Quantity Per Carton | 20 pcs |
| Standard Carton Measurement | 542 x 376 x 388mm (0.079 CBM Per Standard Carton) |
| Standard Carton Gross Weight | 19kg |