

UT71B**Intelligent Digital Multimeters**

CE

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.1%+5)
AC Voltage	2V/20V/200V/1000V	±(0.8%+40)
AC Bandwidth	100KHz	✓
DC Current	200μA/2000μA/20A/200mA/10A	±(1%+20)
AC Current	200μA/2000μA/20A/200mA/10A	±(0.5%+15)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(1.5%+20)
Capacitance	20nF/200nF/2μF/20μF/200μF/2mF/20mF	±(0.1%+20)
Temperature(°C)	-40°C~1000°C	±(0.1%+30)
Temperature(°F)	-40°F~1832°F	±(0.1%+50)
Frequency	20Hz/200Hz/2kHz/20kHz /200KHz/2MHz/20MHz/200MHz	±(0.1%+15)
Duty Cycle	10%~90%	±(1%+30)
4~20mA Loop	0%~100%	±(1%+50)
Special Functions		
Fused 10A Range		✓
Auto Ranging		✓
Current Measurement Alarm		✓

Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Alligator Clip, Test Clip, USB Interface Cable, Software, Carrying Bag
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	542 x 376 x 388mm (0.079 CBM Per Standard Carton)
Standard Carton Gross Weight	19kg