

UT805**Digital Bench-Type Autoranging True RMS Multimeters****SPECIFICATIONS**

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.006%+2)
AC Voltage	200mV/2V/20V/200V/750V	±(0.1%+100)
DC Current	2mA/200mA/10A	±(0.03%+10)
AC Current	2mA/200mA/10A	±(0.3%+100)
Resistance	2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.01%+5)
Capacitance	6nF/60nF/600nF/6μF/60μF/600μF/6mF	±(2%+5)
Frequency	6kHz/60kHz/600kHz/6MHz/600MHz	±(0.1%+3)
Special Functions		
Fused 10A Range	✓	
Auto Ranging	✓	
Voltage & Current : AC+DC Measurement	✓	
AC Voltage Frequency	100kHz True RMS	
Data Store	✓	
Data Recall	✓	
Diode	✓	
Continuity Buzzer	✓	
Max/Min/Avg	✓	
Relative Mode	✓	
Data Hold	✓	
RS232C	✓	
USB	✓	
Full Icon Display	VFD	
Input Impedance for DC Voltage Measurement	200mV & 2V Range : 1GΩ All Other Ranges : 10MΩ	
Max. Display	220000	

GENERAL CHARACTERISTICS

Power	AC220V/50Hz
LCD Size	28 x 128 mm
Product Colour	Red and Grey
Product Net Weight	Around 2.9g (Accessories Net Weight : 0.4kg)
Product Size	240 x 105 x 70mm
Standard Accessories	Test Lead, AC220V Power Cord, English Manual, Alligator Clip, Multi-Purpose Socket, RS232C Interface Cable, USB Interface Cable, Software
Standard Individual Packing	White Box
Standard Quantity Per Carton	4 pcs
Standard Carton Measurement	680 x 445 x 320mm (0.097CBM Per Standard Carton)
Standard Carton Gross Weight	Around 13.16kg

Specifications and other information are subject to change without further notice.