

UT90B

Environmental Friendly Digital MultiMeters

SPECIFICATIONS



Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	±(0.5%+2)
AC Voltage	2V/20V/200V/750V	±(0.8%+5)
DC Current	200µA/2mA/20mA/200mA/10A	±(1%+2)
AC Current	200µA/2mA/20mA/200mA/10A	±(1.2%+5)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+3)
Special Functions		
Fused 10A Range	✓	
Diode	✓	
Continuity Buzzer	✓	
Full Icon Display	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max. Display	1999	

GENERAL CHARACTERISTICS

Power	Charging At AC 230V or AC/DC 12-36V or Solar
LCD Size	60 x 26 mm
Product Colour	UT90B - Grey Holster - Red
Product Net Weight	Around 340g (including holster)
Product Size	179 x 88 x 39 mm
Standard Accessories	Test Lead, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	Around 508 x 433 x 326 mm (Around 0.072 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 22kg

*Available at Extra Cost
Specifications and other information are subject to change without further notice.