

# UT90C

# Environmental Friendly Digital MultiMeters

## SPECIFICATIONS



Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/1000V	±(0.8%+1)
AC Voltage	4V/40V/400V/750V	±(1%+5)
DC Current	400µA/4000µA/40mA/400mA/4A/10A	±(1%+2)
AC Current	400µA/4000µA/40mA/400mA/4A/10A	±(1.5%+5)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(1%+2)
Capacitance	40nF/400nF/4µF/40µF/100µF	±(3%+5)
Frequency	10Hz-10MHz	±(0.1%+3)
<b>Special Functions</b>		
Fused 10A Range	✓	
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
Relative Mode	✓	
Data Hold	✓	
Full Icon Display	✓	
Sleep Mode	✓	
Low Battery Display	✓	
Input Impedance for DC Voltage Measurement	Around 10MΩ	
Max. Display	3999	

## GENERAL CHARACTERISTICS

Power	Charging At AC 230V or AC/DC 12-36V or Solar
LCD Size	60 x 26 mm
Product Colour	UT90C - Grey Holster - Red
Product Net Weight	Around 340g (including holster)
Product Size	179 x 88 x 39 mm
Standard Accessories	Test Lead, English Manual, Holster
Optional Accessories*	Clip-On Test Lead Light (UT-TL), Built-In Test Lead Light (UT-L1), Built-In Test Lead Light Plus (UT-L2)
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	30 pcs
Standard Carton Measurement	Around 508 x 433 x 326 mm (Around 0.072 CBM Per Standard Carton)
Standard Carton Gross Weight	Around 22kg

\*Available at Extra Cost  
Specifications and other information are subject to change without further notice.